



VER-MAC

PCMS-4880 TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-4880 is a mini full-matrix trailer-mounted portable changeable message sign. It features the NTCIP-compliant V-Touch controller, V-Sync Wi-Fi Communication, JamLogic fleet management software. The PCMS-4880 is the most compact unit in our line and provides a lot of flexibility with up to 5 lines of text and 18 characters per line. It's the perfect model to use in urban areas, school zones, lower speed roadways, or for law enforcement, and special events.



V-TOUCH CONTROLLER



4 WAYS TO CHANGE A MESSAGE



AT THE SIGN
Using our V-Touch Controller



NEAR THE SIGN
Using our V-SYNC Wi-Fi



REMOTELY
Using JamLogic on your PC or Laptop



REMOTELY
Using JamLogic Web on your Smartphone or Tablet



JAMLOGIC® FLEET MANAGEMENT SOFTWARE

The PCMS-4880 is equipped with Ver-Mac's high-speed modem with GPS which maximizes your productivity, efficiency and profitability all remotely from your office or home! The JamLogic software is FREE and you get all the updates at no charge!

- Monitor, maintain and manage your signs from any PC, laptop, tablet or smartphone
- View your equipment in a list and GPS map view
- Change a message on one or more signs simultaneously with a simple click
- View your messages and battery voltages
- Group your signs in folders (by customer, location, project... you choose!)
- Receive e-mail or text alerts – optional (low battery cellular failure, etc.)

APPLICATIONS

- City and county (urban areas)
- School zones
- Law enforcement
- Special events

DISPLAY

- Display panel: 36 x 58 in (926 x 1473 mm)
- Panel construction: Aluminum
- Full matrix (48 x 80 pixels)
- Up to 5 lines and 18 characters per line*
- 1 LED per pixel
- Display sign rotates 360 degrees
- Plug & play display modules

*With a 3 x 7 pixel font

WARRANTY

- 1 year on complete trailers
- 2 years on electronic components manufactured by Ver-Mac

DIMENSIONS AND WEIGHTS

- Overall length: 105 in. (2671 mm)
- Overall width: 62 in. (1587 mm)
- Operating height: 158 in. (4013 mm)
- Traveling height: 91 in. (2305 mm)
- Travelling length: 105 in. (2671 mm)
- Weight (approx.): 1370 lb (628 kg)
- Axle/suspension: 2000 lb (909 kg)

OPTIONS

- Battery charger
- Radar
- Data logger (requires radar)
- Tilt-and-Rotate Solar Panels

Other options are available to meet your needs.

HIGH-DEFINITION DISPLAY CARDS

The PCMS-4880 features Ver-Mac's exclusive high-definition display cards that provide a sharper more detailed text and graphic display. The higher degree of clarity allows the PCMS-4880 to be more visible from a distance than other message signs.

POWER SUPPLY CONFIGURATION

SOLAR PANELS

Provide maximum solar recharging during all four seasons.

- Designed to run 12 months in most regions without manual charging
- Various configurations of solar panels and batteries are available to meet your needs.

HIGH-QUALITY CONSTRUCTION

POWDER COATING SUPERIOR FINISH

Impact, humidity, salt spray and rust resistant

4 LEVELING JACKS

For stabilization and easy transportation

REMOVABLE TONGUE

For easy storage

MANUAL LIFT MECHANISM

For a quick deployment

HEAVY-DUTY PLASTIC FENDERS

For durability and easy replacement

PLASTIC BATTERY BOX

To minimize battery corrosion

LOCKABLE CONTROL BOX

For security

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) PINTLE EYE

For easy towing

