PRO SERIES

VER-MAC

PCMS-548LE
TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-548LE PRO Series is a mini full-matrix trailer-mounted portable changeable message sign. The default display is 3 lines and 9 characters (8.75 in.) per line, with the ability of displaying multiple fonts, lines of text and graphics. It features Stealth Technology, NTCIP-compliant V-Touch controller, V-Sync Wi-Fi communication and JamLogic® Fleet Management Software. This unit combines cutting-edge technology, energy-efficient design and high-quality construction to provide the most reliable, cost-effective and safe to operate message sign on the market. The PCMS-548LE PRO Series comes painted in white with radar and modem, which makes it the perfect model for law enforcement.

PRO SERIES FEATURES

STEALTH TECHNOLOGY
Sealed Maintenance-Free Batteries
Anti-Theft Hidden Battery Compartment

V-SYNC WI-FI TECHNOLOGY
Change Messages Via Wi-Fi Using Your Smartphone
Safely Change Messages Out of Traffic.

ROBUST TRAILER DESIGN
Tongue Wheel Jack for safe and easy set up
Controller located away from the road
Rugged Indexed Rod Mast Brake

FULLY-INTEGRATED CELLULAR 4G LTE MODEM
No 3G Upgrade Needed
10-Year Fleet Cell Service
SWZ upgrade (optional)

JAMLOGIC® SOFTWARE
Hourly Automated Refresh and Battery/GPS Alerts & Reports
Interactive Map & List View of All Equipment
Project Folders to Group Equipment
Historical Log of all Locally & Remotely Activated Messages with Date/Time

4 WAYS TO CHANGE A MESSAGE

AT THE SIGN
Using our V-Touch Controller

NEAR THE SIGN
Using our V-SYNC Wi-Fi

REMOTELY
Using JamLogic on your PC or Laptop

REMOTELY
Using JamLogic Web on your Smartphone or Tablet

PCMS-548LE PRO SERIES

POWER SUPPLY CONFIGURATION

SOLAR PANELS
Provide maximum solar recharging during all four seasons.

- Designed to run 12 months in most regions without manual charging
- Various configurations of solar panels and batteries are available to meet your needs.

HIGH-QUALITY CONSTRUCTION

POWDER COATING SUPERIOR FINISH (WHITE)
Impact, humidity, salt spray and rust resistant

4 ADJUSTABLE STABILIZER LEGS
For trailer stabilization and easy transportation

TONGUE WHEEL JACK
To move the trailer around easily

MANUAL LIFT MECHANISM
For a quick deployment

U-SHAPED CRADLE FOR THE SIGN
For better support during transportation

RUGGED INDEXED ROD MAST BRAKE
The sign can be positioned on 209 degrees (17 deg. increments)

HEAVY-DUTY PLASTIC FENDERS
For durability and easy replacement

LOCKABLE PLASTIC BOX
For controller, modem, pump, and other components protection

2-IN. (51 MM) COUPLER OR 3-IN. (76 MM) PINTLE EYE
For easy towing

APPLICATIONS

- City and county (urban areas)
- School zones
- Law enforcement

V-TOUCH CONTROLLER

NTCIP COMPLIANT

EASY-TO-READ
7-inch (178 mm) color LCD touchscreen display screen

USER-FRIENDLY
One-click icon-based menu items

TIME-SAVING
Create your own library of messages

SIMPLE TO OPERATE
The intuitive point-n-go icons ensure quick and easy commands to display or edit messages

ADDITIONAL FUNCTIONALITIES
Scheduling, sign diagnostics, pin-protected security, and much more

DOPPLER RADAR

- Picks up average speed and vehicle count at up to 2000 ft
- Up to 2 lanes / directional
- No calibration necessary
- Integrated into the sign

Transport position

DISPLAY

- Display panel: 45 x 80 in. (1142 x 2026 mm)
- Full matrix of 30 x 56 pixels
- 2 LEDs per pixel
- 5 x 7 pixels (8.75 in.) characters (default)
- 3 lines of 9 characters per line (5 x 7 default font)
- Up to 3 lines of 12 characters per line (3 x 7 font)
- Plug-and-play display modules for simplified maintenance

DIMENSIONS AND WEIGHTS

- Overall length: 133 in. (3367 mm)
- Overall width: 70 in. (1788 mm)
- Travelling height: 91 in. (2308 mm)
- Operating height: 133 in. (3387 mm)
- Weight (approx.): 570 kg (1255 lb)
- Axle/suspension: 909 kg (2000 lb)

OPTIONS

- Battery charger
- Data logger (requires radar)
- Tilt-and-Rotate Solar Panels

Other options are available to meet your needs.

WARRANTY

- 1 year on complete trailer
- 2 years on electronic components manufactured by Ver-Mac

VER-MAC®